

# KAPPACOM E 12 conc.

## Versatile sequestering and dispersing agent

Chemical composition	preparation of polyacrylates and alkyl phosphonates
Appearance	yellowish, nearly clear solution
pH-value 20 °C	4 - 5 (product)
Density 20 °C (g/ml)	approx. 1.19
Ionic charge	anionic

### Function

KAPPACOM E 12 conc. is the concentrated version of KAPPACOM E 12. The product must be diluted with half quantity of water to get KAPPACOM E 12.

KAPPACOM E 12 conc. has an excellent dispersing effect and is an efficient sequestering agent for alkaline earth and heavy metal ions. At pH 11 and 60 °C, 1 g of KAPPACOM E 12 conc. binds approx. 180 mg of CaO or approx. 320 mg of CaCO<sub>3</sub>. The formed complexes are very stable even at boiling temperature and in a stronger alkaline range (to approx. 3 g/l NaOH 100 %).

KAPPACOM E 12 conc. does not cause any demetallization of direct and reactive dyes based on metallic complexes in spite of its strongly developed chelating capacity.

KAPPACOM E 12 conc. is not interfacial-active and therefore foam-free.

### Application

KAPPACOM E 12 conc. is a very versatile product, e. g.

- for dyeing of cellulosic fibres or their blends with direct, reactive, vat and sulfur dyes. It is possible to dye raw cotton without preliminary cleaning for example.
- for printing with reactive dyes when applying alginate thickening agents.
- for all scouring, washing and soaping processes in neutral and alkaline range.

Recommended application level for long liquors depending on the respective operating conditions:

- approx. 0.05 ml/l KAPPACOM E 12 conc.

Relating to the sequestering of water hardness, approx. 0.05 ml KAPPACOM E 12 conc. is required per 1 °dH and 1 litre of water.

### Dilution instruction

KAPPACOM E 12 conc. can be diluted with cold water at any ratio. The product can also be added directly to the liquor.

### Storage

KAPPACOM E 12 conc. remains stable for at least 1 year if stored properly and cool in a tightly closed container.

### Contact

**KAPP Chemie**  
info@kapp-chemie.com  
+49 / 6772 / 9311-0



### Standards (further on request)

- GOTS
- OEKOTEX Standard 100
- ZDHC