

KAPPAMID EH 72

Polymer dispersion

Chemical composition	polyvinylacetate dispersion
Appearance	white emulsion
pH-value 20 °C	3 - 5 (product)
Density 20 °C (g/ml)	approx. 1.0
Ionic charge	nonionic

Function

KAPPAMID EH 72 is a wash-fast finishing agent and filler for all types of fibres including glass fibre. The product forms a thermoplastic, light-fast and adhesive film. Depending on the application level and the fabric, KAPPAMID EH 72 gives a full and harsh handle.

The product is not suitable for applications where stability to alkali is necessary.

Application

Recommended application level:

Resin finishing

- 20 – 50 g/l KAPPAMID EH 72
- Drying at 150 – 160 °C

Fibreglass roof shetting

- 70 – 100 g/l KAPPAMID EH 72
- in combination with starch and repellent agents
- Padding or nip padding
- Liquor pick-up: 100 – 120 %
- Drying at 150 °C

Dilution instruction

KAPPAMID EH 72 can be mixed with water at any ratio.

Storage

KAPPAMID EH 72 remains stable for at least 6 months if stored properly in a tightly closed original container.

Protect against frost!

Contact

KAPP Chemie
info@kapp-chemie.com
+49 / 6772 / 9311-0

