

# Technical Data Sheet

## RADIASIL® 2002

### General Description

- A clear  $\gamma$ -silane terminated hybrid polyurethane pre-polymer. RADIASIL 2002 is a moisture curing material that combines elasticity and mechanical strength properties which is perfectly suitable for producing adhesives.

### Applications

- Building & Construction Adhesives
- Industrial Adhesives
- Low modulus Sealants
- Flooring installation

### Key Features

- High durability
- Good reactivity
- Broad adhesion profile
- Low cold flow

Physical properties	
Physical state of material	Clear, no lumps
NCO-value	<0.1%
Viscosity Brookfield CAP 2000+ (spl3,20rpm,25°C)	40 000-100 000 @25°C, (mPa.s)

Test methods and Certificate of Analysis (COA) available on request.

### Storage & shelf life:

6 months when kept in closed original packaging at ambient temperature.

Product is sensitive to moisture, condition containers after opening.

### Packaging types:

200KG Drum / 1000kg IBC

Disclaimer: Our technical advice, information, statements, whether given verbally, in writing, or in the form of test results, is offered for your guidance without warranty. No warranty for fitness for a particular purpose is made. This also applies where protective rights of third parties are involved. It does not release the user from obligation to test the suitability of the products and formulas for the intended process and applications. Our guarantee is limited to the consistent quality of our product.